

## Features

- Differential output HCSL
- Frequency range from 25MHz to 200MHz
- 2.5V /3.3V operation voltage
- Excellent low phase noise and jitter
- 3-state function available
- Automatic mounting and reflow soldering
- Applications: *Fiber channel, Ethernet, Server SONET, ATA, SCSI devices, etc*
- RoHS Compliant & Pb Free




## Standard Specifications

Type	3H SMD 3225 HCSL DifferentialOscillator
Output Type	HCSL
Output Load	50Ω
Supply Voltage	2.5V / 3.3V
Frequency Range	25~200 MHz
Supply Current	30mA Max.
Overall Frequency Stability*	±50ppm, or specify
Operating Temperature	-40~+85°C, or specify
Storage Temperature	-55~+125°C
Voltage Vol (Max.) / Voh (Min.)	0mV / 740mV
Rise (Tr) / Fall (Tf) Time	0.5ns Max.
Start-up Time	10ms Max.
Duty Cycle	45~55%
Phase Noise (156.25MHz) at 1KHz	-120dBc/Hz
Phase Jitter (12KHz~20MHz)	1ps Max.
Aging (at 25°C)	±3ppm /Year Max.
Packing Units	3000pcs. /Reel

\* Including frequency tolerance at 25°C, variation over temperature, supply voltage variation, aging and vibration.

## Dimensions [mm]



### Pin Connections

Pin No.	Connection
1	OE or NC
2	OE or NC
3	GND
4	Output
5	Comp. Output
6	Vcc

