

Features


- 3225 size, low profile of 1.0mm
- Frequency range from 1MHz to 125MHz
- Low voltage operation
- Low current consumption
- 3-state function
- Automatic mounting and reflow soldering
- Applications: *Automotive, GPS, Bluetooth, PC, IoT, PDA, Peripherals, DVC, etc.*
- RoHS Compliant & Pb Free



Standard Specifications

Type	3N SMD Crystal Oscillator
Output Type	CMOS
Output Load	15pF, or specify
Supply Voltage	1.8~3.3V
Frequency Range	1~125 MHz
Supply Current	15mA Max.
Frequency Stability	±25ppm, ±30ppm
Operating Temperature	-40~+85°C, or specify
Storage Temperature	-55~+125°C
Voltage Vol (Max.) / Voh (Min.)	0.1VDD / 0.9 VDD
Rise (Tr) / Fall (Tf) Time	5ns Max.
Period Jitter	40ps Max.
Duty Cycle	45~55%
Start-up Time	5ms Max.
Phase Jitter (12KHz~20MHz)	1ps Max.
Aging (at 25°C)	±3ppm /Year Max.
Packing Units	3000pcs. /Reel

Dimensions [mm]



Pin Connections

Pin No.	Connection
1	OE (Output Enable)
2	GND
3	Output
4	Vcc

